



8" Industrial Barcode Printer

# HD830i

The best-in-class eight inch wide industrial barcode printer. Perfect for wide format labels.

GoDEX's HD830i is an eight-inch barcode printer designed for applications that require large and durable labels. The HD830i is a rugged printer of exquisite design which includes significant characteristics of high performance electronics, reliable mechanism, user -friendliness and easy maintenance design.



External Label Stand :10" Max.  
(Standard Package included)

- 3.2" color touchscreen facilitates intuitive navigation. Adjustable to 15°.
- Dual-Colored status LEDs and calibration button for simplicity.
- Robust metal casing and solid print mechanism to take on heavy duty jobs
- Outstanding breadth: max label width 10"/ Max print width 8.57".
- Optional wireless connectivity: Bluetooth or Wi-Fi module
- Top cover designed for ease of motion: heightened safety and comfort.
- A sturdy external label stand for up to 10" roll diameters included.
- Adjustable media detectors: including reflective and see-through sensors
- Advanced adaptive dampening technology : to optimize print quality
- Internal Media Pressure plate is designed to stabilize the label printing process

# GoDEX

# HD830i Specifications

Model Name		HD830i
<b>Print Method</b>		Thermal Transfer / Direct Thermal
<b>Resolution</b>		300 dpi (12 dot/mm)
<b>Print Speed</b>		4 ips (102 mm/s)
<b>Print Width</b>		8.64" (219.5mm)
<b>Print Length</b>		Min. 1" (25.4 mm)** ; Max . 40" ( 1,016 mm)
<b>Processor</b>		32-bit RISC CPU
<b>Memory</b>	<b>Flash SDRAM</b>	128 MB Flash (60 MB for user storage) 32 MB
<b>Sensor Type</b>		Adjustable reflective sensor and Adjustable transmissive sensor
<b>Media</b>	<b>Type</b>	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
	<b>Width</b>	Tear : Min. 4" (108 mm) – Max. 10" (255 mm) Cutter : Max. 8.5" (215.9 mm)
	<b>Thickness</b>	Min. 0.002" (0.06 mm) – Max. 0.01" (0.25 mm)
	<b>Media Capacity</b>	Media OD up to 10" Max.
<b>Ribbon</b>	<b>Types</b>	Wax, wax/resin, resin
	<b>Length</b>	Max.981' (300 m)
	<b>Width</b>	Min. 4.3" (110 mm) – Max. 8.66" (220 mm)
	<b>Ribbon roll diameter</b>	2.67" (68 mm) Max.
<b>Printer Language</b>	<b>Core diameter</b>	1" (25.4 mm)
		EZPL, GEPL, GZPL auto switch
<b>Software</b>	<b>Label design software</b>	GoLabel (for EZPL only)
	<b>Driver</b>	Windows 2000, XP, Vista, Windows 7, 8.1 and 10 , Windows Server 2003 , 2008 & 2010 MAC · Linux
	<b>DLL</b>	Win CE, .NET, Andriod, Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1/Windows 10
<b>Resident Fonts</b>	<b>Bitmap Fonts</b>	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	<b>TTF Fonts</b>	Bitmap fonts 8 times expandable in horizontal and vertical directions TTF Fonts (Bold / Italic / Underline ). 0°,90°, 180°, 270° rotatable
<b>Download Fonts</b>	<b>Bitmap Fonts</b>	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese (GB2312), Japanese (S-JIS), Korean (KS-X1001)
	<b>Asian Fonts</b>	90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions TTF Fonts (Bold / Italic / Underline ). 0°,90°, 180°, 270° rotatable
<b>Barcodes</b>	<b>1-D Bar Codes</b>	China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8, EAN-13, EAN 8/13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5 , Interleaved 2-of-5 (12 of 5), Interleaved 2- of 5 with Shipping Bearer Bars, ISBT – 128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Random Weight, Standard 2 of 5, Telepen, UPC-A, UPC-E, UPC-A and UPC-E with EAN 2 or 5 digit extension, UCC 128, UCC/EAN-128 K-Mart
	<b>2-D Bar Codes</b>	Aztec code, Code 49, Codablock F , Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39 Codepage 437, 737, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode UTF8 · UTF16BE · UTF16LE
<b>Code Pages</b>		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
<b>Graphics</b>		<ul style="list-style-type: none"> <li>• USB 2.0 (B-Type)</li> <li>• Serial port: RS-232 (DB-9)</li> <li>• IEEE 802.3 10/100 Base-Tx Ethernet port (RJ-45)</li> <li>• USB Host (A-Type)</li> <li>• Backlight 3.2" touch screen LCD</li> <li>• 1 Power on/standby button with dual colour LED backlight</li> <li>• 1 FEED / PAUSE / CANCEL button with dual colour LED : Ready (Green); Error (Red)</li> <li>• 1 Calibration button at rear panel</li> </ul>
<b>Interfaces</b>		
<b>Control Panel</b>		
<b>RTC</b>		Standard
<b>Power</b>		Auto Switching 100-240V AC, 50-60Hz
<b>Environment</b>	<b>Operation Storage</b>	41°F to 104°F (5°C to 40°C), 20-85%, non-condensing -4°F to 140°F (-20°C to 60°C), 10-90%, non-condensing
<b>Agency Approvals</b>		CE (EMC) · FCC Class B · CB · UL · cUL · CCC
<b>Dimension</b>	<b>Length x Width x Height</b>	221 mm x 431 mm x 224 mm
	<b>Weight</b>	11.7 Kg, excluding consumables Cutter (Dealer Install)
<b>Options</b>		Parallel port adaptor module (Centronic female 36-pin)(Dealer Install) Bluetooth (Dealer Installer) Wireless LAN (IEEE 802.11 b/g/n) (Dealer Install)

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

\*\* Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. GoDEX is pleased to test non-standard materials for minimum print height, and maximum print speed capability.