

Product data FASSON Vellum Extra / S2045 / BG40 brown

No Imprint / [VA0941](#)

EAN Code :

8712739029918

Spec Code : AG727

Issue date : 6-Jul-2006

FaceStock

A white, surface-sized, supercalendered woodfree printing paper.

Basis Weight	73g/m ²	ISO 536
Caliper	0.071mm	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis Weight	60g/m ²	ISO 536
Caliper	0.055mm	ISO 534
Transparency	47%	DIN 53147

Laminate

Total Caliper	0.141
---------------	-------

PERFORMANCE DATA

Initial Tack	720N/m	FTM 9 glass
Peel Adhes. 90°	400N/m	FTM 2 st.st.

Min. appl. temp.	-5 °C
Service temp.	-40 °C / +70 °C

N.B. : All data to be considered as typical values.

Adhesive performance

The adhesive features excellent tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates.

Particularly good performance at lower temperatures, e.g. labeling of chilled products.

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XXI as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

Applications and use

Typical applications include labels for supermarkets, food packaging, catchweigh, cosmetics, toiletries, chemical products and promotional labeling.

Conversion / Printing

Facestock provides excellent print quality by all the usual printing technologies.

Excellent conversion characteristics in rotary and flat-bed.

Temperatures up to 80°C can be used for ink drying, provided the web temperature is below 50°C when it reaches the waste stripping station.

Shelf life

Two years when stored at 22°C / 55% RH.

